

Rubber Fab

a Garlock Hygienic Technologies company

RFACSG



Part Number	Clamp Size	Length (inches)	Max. Cold Working Pressure PSI @70°F	Pressure PSI @ Max. Allowable Temp. @140°F	Inside Diameter (Reference ID)	Outside Diameter (Reference OD)
24RFACSG-5.875	1.5"	5.875	145	100	1.295"	2"
32RFACSG-5.875	2"	5.875	145	100	1.835"	2.625"
48RFACSG-7.50	3"	7.500	120	75	2.817"	3.625"
64RFACSG-7.625	4"	7.625	75	30	3.750"	4.750"

Note:

Standard length shown, other lengths available upon request. Maximum length for 1 1/2" and 2" sizes = 48". Maximum lengths for 3" and 4" sizes = 7.625"

Clear Acrylic Sight Tubes

Made from ASTM 5436-D, FDA-conforming acrylic and can be clamped into sanitary lines seamlessly.

Not recommended for use with abrasive products. Do not use 2 bolt high-pressure clamps. Minimum length is 1.25" OAL

Features

- Ideal for simple sight requirements as well as tank level indication
- Economical option to standard stainless steel sight glasses
- Standard clamp torque is required (25 in/lbs)
- Pressure ratings absent thermal shock

Certifications

- CFR 177.1010