


Rubber Fab

a Garlock Hygienic Technologies company

RFST



Smoothbore PTFE Lined Hose with Stainless Steel Braided Cover

TUBE: Seamless white PTFE

COVER: Braided stainless steel

TEMPERATURE: -20°F to 350°F

Part Number	Hose ID Inch	Hose OD Inch	Bend Radius Inch	Max. Working Pressure @ 70°F psig	Vacuum Rating @ 70°F in. Hg.	Weight Per Foot
04RFST	0.25	0.37	3.00	3000	FULL	0.08
06RFST	0.38	0.51	5.00	2000	FULL	0.11
08RFST	0.50	0.63	6.50	1425	FULL	0.16
12RFST	0.75	0.88	8.20	1000	FULL	0.20
16RFST	1.00	1.19	12.00	1000	FULL	0.50
24RFST	1.50	1.76	20.00	900	FULL	0.92

Features

- Outer cover is stainless steel braid overwrap
- Smoothbore PTFE inner core
- Non-stick contact surface will not contaminate product
- Withstands high velocity and pressure surges
- Resists moisture
- Autoclavable

Applications

- Food and beverage processing
- Pharmaceutical processing
- Cosmetics
- Hot CIP solutions
- Chemical products
- Low pressure steam

Hose Certifications

- USP Class VI
- FDA 21 CFR 177.1550
- USDA

26 Brookfield Drive • Sparta, New Jersey 07871

973.579.2959 • 866-442-2959 Toll Free • 973.579.7275 Fax • www.rubberfab.com